



MODEL: DL DECK LIGHT CURVE

APPLICATION:

- Decks, Fences, Benches, Steps, Wall Sconces, etc

CONSTRUCTION:

- 6061 Aluminum – High Performance Enamel (AB, BLK, WHT Models)
- 6061 Aluminum – Clear Anodized (SSA Model)

LED LIFE EXPECTANCY (TM-21 DATA):

- Greater than 60,000 hours (greater than 20 years at 8 hours per day)

DRIVER SYSTEM:

- Internal Driver constructed with advanced electronic components

INPUT VOLTAGE RANGE:

- 10.5 to 18 Volts AC or DC

DELIVERED LUMENS (3000K):

IES FILES AVAILABLE UPON REQUEST

- 1.5 VA- 109 lm

INSTALLATION AND HARDWARE:

- All stainless steel hardware

LEAD WIRES:

- UL1015 22 AWG Tinned Copper Wire
- 60 inch length

ELECTRONICS WARRANTY:

- 20 Years

CERTIFICATION:

- UL1838 Low Voltage Landscape Lighting

POWER CONSUMPTION/AVAILABLE MODELS:


- See Power Consumption / Model Availability Table (next page)

AVAILABLE FINISHES:

- Architectural Bronze (AB) • White (WHT)
- Black (BLK) • Stainless Aluminum (SSA)

ORDERING CODES

(CHOOSE 1 ITEM FROM EACH COLUMN BELOW) EX: DL15 CURVE AB



Model #	Wattage	Optics	Finish	Light Output	
DL CURVE	15	130°	AB	(blank) 3000K Warm White	
			BLK	2700K 2700K Warm White	
			WHT	5000K 5000K Neutral White	
			SSA	AMB Amber	
			BLU	Blue	
			RBL	Royal Blue	
			GRN	Green	
			RO	Red Orange	
			RED	Red	
			ER	Extreme Red	





POWER CONSUMPTION / MODEL AVAILABILITY

Light Output	15W	
	Watts	VA
3000K	1.2	1.5
2700K	1.2	1.5
5000K	1.2	1.5
AMB	0.9	1.1
BLU	1.2	1.5
RBL	1.2	1.5
GRN	1.2	1.5
RO	0.9	1.1
RED	0.9	1.1
ER	0.9	1.1

■ Dark gray background indicates stock items. Non-stock items require a 10 business day lead time.