

MODEL: MM MICRO MAX (MICRO II SERIES)

APPLICATION:

- Fresh Water Submersible/Wet Applications (No chlorine/harsh chemicals)
- Decks, Railings, Gazebos, Statues, Planters, Lanais, Fences, Benches,...

CONSTRUCTION:

- 6061 Aluminum – Black Anodized (BLK Model)
- High Performance C360 Solid Brass (BR Model)

LED LIFE EXPECTANCY (TM-21 DATA):

- Greater than 60,000 hours (greater than 20 years at 8 hours per day)

DRIVER SYSTEM:

- Internal Driver constructed with advanced electronic components

INPUT VOLTAGE RANGE:

- 10.5 to 18 Volts AC or DC

DELIVERED LUMENS (3000K): IES FILES AVAILABLE UPON REQUEST

- 1.5 VA- 109 lm

INSTALLATION AND HARDWARE:

- All stainless steel hardware

LEAD WIRES:

- UL1015 22 AWG Tinned Copper Wire
- 60 inch length

ELECTRONICS WARRANTY:

- 20 Years

CERTIFICATION:


- UL1838 Low Voltage Landscape Lighting

POWER CONSUMPTION/AVAILABLE MODELS:

- See Power Consumption / Model Availability Table (next page)

AVAILABLE FINISHES:


- Black (BLK) • C360 Solid Brass (BR)



BLK



BR



ORDERING CODES

(CHOOSE 1 ITEM FROM EACH COLUMN BELOW) EX: MM15-II BLK

Model #	Wattage	Optics	Finish	Light Output	
MM	1.2	-II (130°)	BLK	(blank) 3000K Warm White	
			BR	2700K 2700K Warm White	
				5000K 5000K Neutral White	
			AMB	Amber	
			BLU	Blue	
			RBL	Royal Blue	
			GRN	Green	
			RO	Red Orange	
			RED	Red	
			ER	Extreme Red	



POWER CONSUMPTION / MODEL AVAILABILITY

Light Output	1.2 W	
	Watts	VA
3000K	1.2	1.5
2700K	1.2	1.5
5000K	1.2	1.5
AMB	0.9	1.1
BLU	1.2	1.5
RBL	1.2	1.5
GRN	1.2	1.5
RO	0.9	1.1
RED	0.9	1.1
ER	0.9	1.1

■ Dark gray background indicates stock items. Non-stock items require a 10 business day lead time.